

HELMHOLTZ RESEARCH FOR
GRAND CHALLENGES

Helmholtz - OCPC - Programme 2017-2021
for the Involvement of Postdocs in Bilateral Collaboration
Projects with China

PART A

Title of the project

Multiphase-field modelling of Asaro – Tiller – Grinfeld instability in Allen – Cahn framework

Helmholtz Centre and institute

Karlsruhe Institute of Technology (KIT), Institute of Applied Materials (IAM)

Project leaders


Dr. P. G. Kubendran Amos, IAM, KIT

Dr. D. Schneider, IAM, KIT

Prof. Dr. B. Nestler, IAM, KIT

Web-address:

www.iam.kit.edu/cms/



Description of the project:

In the fabrication of nanostructured semiconductors, which are the integral part of modern lasers and diodes, molecular beam epitaxy (MBE) plays a critical role [1]. MBE involves vaporising the source material, and conscientiously depositing it onto a substrate in the form a 'beam'. Even though a precise control on the chemical composition of the processed material is rendered by MBE, an elastic instability is frequently associated with it [2]. This instability is referred to as Asaro – Tiller – Grinfeld (ATG) instability [3,4].

The difference in lattice parameters of the source material and substrate, along with disparity in the temperature, introduces non-hydrostatic loading as misfit strain and thermal expansion. Relaxation of this strain induces morphological changes which alter the configuration of the interface. Accordingly, *ATG instability* is characteristically associated with the morphological evolution of the interface under the combined influence surface – and elastic – energy, which is introduced by non-hydrostatic loading.

Owing to its noticeable effect on the processing of multi-layered semiconductors, *ATG instability* is extensively analysed [5]. In addition to experimental techniques, theoretical treatments have been adopted to understand interplay of surface – and elastic – energy in governing the configuration of the interface. Recently, morphological evolution of the interface associated with *ATG instability* has been modelled in phase-field framework [6,7,8]. Despite several advancements, this instability in phase-field approach is invariably modelled by treating the order parameter as a conserved variable, and consequently, solving its temporal evolution in Cahn – Hilliard framework. This treatment, in addition to being numerically arduous, is also computationally expensive. Alternatively, *ATG instability* can efficiently be modelled by solving the evolution of order-parameter in Allen – Cahn framework, by separately imposing the necessary constraints. Correspondingly, the proposed work aims to develop a computationally – efficient approach for phase-field modelling of morphological changes accompanying *ATG instability*.

In the proposed research, the candidate will investigate *ATG instability* in two separate frameworks. One would involve coupling elastic energy-density with redistribution energy [9,10,11], while the other would replace the redistribution energy with a volume – preserving bulk contribution [12]. While both these techniques treat order parameter as a non – conserved variable, the latter adopts a quasi – Allen – Cahn framework [13]. By examining these different techniques for thermodynamic consistency, and computational efficiency, this work would ultimately indicate an efficient approach for phase-field modelling of *ATG instability*. Furthermore, effects of different modes of mass transfer including surface and volume diffusion on the morphological evolution will be encompassed in this research.




References

- [1] W P McCray, MBE deserves a place in the history books, *Nature nanotechnology*, 2(5):259, 2007.
- [2] A Danescu, The Asaro – Tiller – Grinfeld instability revisited, *International journal of solids and structures*, 38(26): 4671 – 4684, 2001.
- [3] R J Asaro and W A Tiller, Interface morphology development during stress corrosion cracking: Part I via surface diffusion, 3(7): 1789 – 1796, 1972.
- [4] M A Grinfeld, Instability of the interface between a non-hydrostatically stressed elastic and a melt, *DoSSR*, 290(6): 1358 – 1363, 1986.
- [5] A Krost, C Berger, P Moser, J Blasing, A Dadgar, C Hums, T Hempel, B Bastek, P Veit and J Christen, Stranski – Krastnov transition and self – organized structures in low – strained AlInA/GaN multilayer structures, *Semiconductor science and technology*, 26(1), 2010.
- [6] K Kassner and C Misbah, A phase – field approach for stress – induced instabilities, *Europhysics Letters*, 46(2), 1999.
- [7] D H Yeon, P R Cha and M Grant, Phase - -field model of stress – induced surface instabilities: surface diffusion, 54(6): 1623 – 1630, 2006.
- [8] B G Chirranjeevi, T A Abinandanan and M P Gururajan, A phase – field study of morphological instabilities in multilayer thin film, *Acta Materialia*, 57(4): 1060 – 1067, 2009.
- [9] D Schneider, O Tschukin, A Choudhury, M Selzer, T Boehlke and B Nestler, Phase – field elasticity model based on mechanical jump conditions, *Computational Mechanics*, 55(5): 887 – 901, 2015.
- [10] D Schneider, E Schoof, O Tschukin, A Reiter, C Herrmann, F Schwab, M Selzer and B Nestler, Small strain multiphase – field model accounting for configurational forces and mechanical jump conditions, *Computational Mechanics*, 61(3): 277 – 295, 2018.
- [11] B Nestler, F Wendler, M Selzer, B Stinner and H Garcke, Phase – field model for multiphase systems with preserved volume fractions, *Physical Review E*, 78(1), 2008.
- [12] P G K Amos, L T Mushongera and B Nestler, Phase – field analysis of volume – diffusion-controlled shape – instabilities in metallic systems – I: 2 – dimensional plate – like structures, *Computational Material Science*, 144: 363 – 373, 2018.
- [13] P G Kubendran Amos, E Schoof, J Santoki, D Schneider and B Nestler, Limitations of preserving volume in Allen – Cahn framework for microstructural analysis, *Computational Material Science*, 173, 2020.

Description of existing or sought Chinese collaboration partner institute:

This proposal is not designated to any specific partner institute but is rather intended as a public call whereby interested PhD scholars can apply, and the subsequent shortlisting will be done based on their research experience.



Required qualification of the post-doc:

- PhD in Material Science, Mechanical Engineering, Physics or any related fields with thesis involving phase – field or other analogous numerical modelling techniques
- Experience in developing and implementing numerical models preferably in C, C++ or Python is highly desired.
- Additional skills include convincing communication skills, and ability to work independently towards the proposed goal.

PART B

Documents to be provided by the post-doc, necessary for an application to OCPC via a postdoc-station in China, which is affiliated to a research institution like a university:

- Detailed description of the interest in joining the project (motivation letter)
- Curriculum vitae, copies of degrees
- List of publications
- 2 letters of recommendation
- Proof of command of English language

PART C

Additional requirements to be fulfilled by the post-doc:

- Max. age of 35 years
- PhD degree not older than 5 years
- Very good command of the English language
- Strong ability to work independently and in a team